


## SLP025-12U

High Efficiency Multicrystalline PV Module

Electrical Characteristics	SLP025-12U
Product code	025011203A
Maximum power (Pmax)	25W
Voltage at Pmax (Vmp)	17.2V
Current at Pmax (Imp)	1.45A
Open-circuit voltage (Voc)	21.6V
Short-circuit current (Isc)	1.60A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/°C
Temperature coefficient of power	-(0.5±0.05)%/°C
NOCT (Air 20°C; Sun 0.8kW/m <sup>2</sup> wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%



\*STC: Irradiance 1000W/m<sup>2</sup>, AM1.5 spectrum, module temperature 25°C

\*NOCT: Nominal operating cell temperature (the data is only for reference)




### Module Diagram

Dimensions in brackets are in inches.  
Un-bracketed dimensions are in millimeters.  
Unit: mm[in.]



Junction Box  
Top View(Lid Open)




Section A-A

### Features

- Nominal 12V DC for standard output.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

### Characteristics



SLP025-12U I-V Curves

Specifications	SLP025-12U
Cells	Polycrystalline silicon solar cell
No. of cells and connections	36(2X18)
Module dimension	675mm[26.57in.].x357mm[14.06in.].x30mm[1.18in.]
Weight	3.3kg[7.28lbs]
Packing information(Carton)	705mm[27.76in.].x210mm[8.27in.].x385mm[15.16in.]/(5pcs/ctn)

\*Limited warranty: 2-year limited warranty of materials and workmanship; 10-year limited warranty of 90% power output; 25-year limited warranty of 80% power output. For detail, please contact us.

\*Specifications are subject to change without notice at any time.